



# Material Safety Data Sheet

## 1. PRODUCT AND COMPANY IDENTIFICATION

### AMBERLITE(TM) MB9L Resin/BASE BULK

Revision date: 10/04/2004

**Supplier** Rohm and Haas Company  
100 Independence Mall West  
Philadelphia, PA 19106-2399 United States of America

**For non-emergency information contact:** 215-592-3000

#### Emergency telephone number

Spill Emergency 215-592-3000  
Health Emergency 215-592-3000  
Chemtrec 800-424-9300

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Strong acid cation exchange polymer, hydrogen ion form	Not Hazardous	20.0 - 30.0%
Strong base anion exchange polymer, hydroxide ion	Not Hazardous	12.0 - 22.0%
Water	7732-18-5	48.0 - 68.0%

## 3. HAZARDS IDENTIFICATION

### Emergency Overview

#### Appearance

Form Beads  
Colour gold

#### Hazard Summary

#### **CAUTION!**

MAY CAUSE EYE/SKIN IRRITATION.

#### Potential Health Effects

**Primary Routes of Entry:** Skin contact  
Eye contact

**Eyes:** Direct contact with material can cause the following:  
slight irritation

**Skin:** Prolonged or repeated skin contact can cause the following:  
slight irritation

## 4. FIRST AID MEASURES

**Skin contact:** Wash off with soap and water. If skin irritation persists, call a physician.

**Eye contact:** Rinse with plenty of water. If eye irritation persists, consult a specialist.

---

## 5. FIRE-FIGHTING MEASURES

---

<b>Flash point</b>	not applicable
<b>Ignition temperature</b>	500.0 °C (932.00 °F)
<b>Lower explosion limit</b>	not applicable
<b>Upper explosion limit</b>	not applicable
<b>Suitable extinguishing media:</b>	Use the following extinguishing media when fighting fires involving this material: water spray carbon dioxide (CO <sub>2</sub> ) foam dry chemical

**Specific hazards during fire fighting:**Toxic fumes are generated when material is exposed to fire or fire conditions. Cool closed containers exposed to fire with water spray.

**Special protective equipment for fire-fighters:**In the event of fire, wear self-contained breathing apparatus.

**Further information:**Remain upwind.  
Avoid breathing smoke.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### Personal precautions

Appropriate protective equipment must be worn when handling a spill of this material. See SECTION 8, Exposure Controls/Personal Protection, for recommendations.

If exposed to material during clean-up operations, see SECTION 4, First Aid Measures, for actions to follow.

### Methods for cleaning up

Keep spectators away.

Floor may be slippery; use care to avoid falling.

Transfer spilled material to suitable containers for recovery or disposal.

---

## 7. HANDLING AND STORAGE

---

### Handling

NOTE: This product as supplied is a whole bead resin and may produce slight eye irritation. However, the ground form of this resin should be treated as a severe eye irritant. Worker exposure to ground resins can be controlled with local exhaust ventilation at the point of dust generation, or use of suitable personal protective equipment (dust/mist air-purifying respirator and safety goggles). Avoid repeated freeze-thaw cycles; beads may fracture. If frozen, thaw at room temperature. Properly designed equipment is vital if these resins are to be used in conjunction with strong oxidizing agents such as nitric acid to prevent a rapid build-up of pressure and possible explosion. Consult a source knowledgeable in the handling of these materials before proceeding.

### Storage

#### Further information:

CAUTION: Do not pack column with dry ion exchange resins. Dry beads expand when wetted; this expansion can cause glass column to shatter.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### Exposure limit(s)

Exposure limits are listed below, if they exist.

**Eye protection:**Use safety glasses with side shields (ANSI Z87.1 or approved equivalent).

**Hand protection:**Cotton or canvas gloves.

**Respiratory protection:**No personal respiratory protective equipment normally required.

**Protective measures:**Facilities storing or utilizing this material should be equipped with an eyewash facility.

**Engineering measures:**None required under normal operating conditions.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Appearance

<b>Form</b>	Beads
<b>Colour</b>	gold
<b>Boiling point/range</b>	100 °C (212.00 °F) Water
<b>Melting point/range</b>	0 °C (32 °F) Water
<b>Flash point</b>	not applicable
<b>Ignition temperature</b>	500 °C (932.00 °F)
<b>Lower explosion limit</b>	not applicable
<b>Upper explosion limit</b>	not applicable
<b>Water solubility</b>	practically insoluble
<b>Relative density</b>	0.75
<b>Percent volatility</b>	48 - 68 %

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

<b>Hazardous reactions</b>	Stable under normal conditions.
<b>Materials to avoid</b>	Avoid contact with the following: Strong Oxidizers nitric acid
<b>Hazardous decomposition products</b>	Thermal decomposition may yield the following: monomer vapors,
<b>polymerization</b>	Product will not undergo polymerization.

---

## 11. TOXICOLOGICAL INFORMATION

---

No data are available for this material. The information shown is based on profiles of compositionally similar materials.

<b>Acute oral toxicity</b>	LD50rat >5,000 mg/kg
<b>Acute dermal toxicity</b>	LD50rabbit >5,000 mg/kg

---

## 12. ECOLOGICAL INFORMATION

---

<b>Chemical Fate</b>	
<b>Biochemical Oxygen Demand (BOD)</b>	not applicable

---

## 13. DISPOSAL CONSIDERATIONS

---

### Disposal

**Waste Classification:**When a decision is made to discard this material as supplied, it does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC), however, has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP). Unused material may be incinerated or landfilled in facilities meeting local, state, and federal regulations.

**Contaminated packaging:**Empty containers should be taken to local recyclers for disposal. Refer to applicable federal, state, and local regulations.

---

## 14. TRANSPORT INFORMATION

---

### DOT

Not regulated for transport

### IMO/IMDG

Not regulated (Not dangerous for transport)

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations

## 15. REGULATORY INFORMATION

### Workplace Classification

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR1910.1200).

This product is not a 'controlled product' under the Canadian Workplace Hazardous Materials Information System (WHMIS).

**SARA TITLE III:Section 311/312 Categorizations (40CFR370):**This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

### SARA TITLE III:Section 313 Information (40CFR372)

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

### CERCLA Information(40CFR302.4)

Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

**US. Toxic Substances Control Act (TSCA)** All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

### Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

## 16. OTHER INFORMATION

### Hazard Rating

	Health	Fire	Reactivity
<b>HMIS</b>	1	1	0

### Legend

ACGIH	American Conference of Governmental Industrial Hygienists
BAC	Butyl acetate
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit (STEL):
TLV	Threshold Limit Value
TWA	Time Weighted Average (TWA):
	Bar denotes a revision from prior MSDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Print Date:

Version:1.2

10/05/2004

Layout 209990